# CENTRAL INTELLIGENCE AGENCY

# INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Socious 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

### SECRET

### SECURITY INFORMATION

COUNTRY

Bulgaria

REPORT NO.

25X1A

SUBJECT

Military Installations in Elkhovo Area
25X1A

DATE OF INFO.

REQUIREMENT NO. RD

PLACE ACQUIRED

REFERENCES

THE SOURCE EVALUATIONS IN THIS REPORT ARE DEFINITIVE.

THE APPRAISAL OF CONTENT IS TENTATIVE.

(FOR KEY SEE REVERSE)

SOURCE: 25X1X

### Line of Fortifications

 A line of fortifications extends between Elkhovo and Fakiya (N 42-12, E 27-04).

(A sketch based on a free-hand drawing made by informant and showing these fortifications is included as Appendix A on page 4).

- 2. Firing positions are located at 20 to 40 meter intervals, and are  $60 \times 40$  centimeters in size. (See Figure #1, Appendix B on page 5).
- 3. The fortification line is 1.2 meters wide at the top, 50-60 centimeters wide at the bottom, and 1.2-1.3 meters deep. The turns in the fortification line are at 15-20 meter intervals. A "few" fortification lines are 1.4 meters wide at the top, 60-70 centimeters wide at the bottom, and 1.2-1.3 meters deep, with turns at 15-20 meter intervals. (See Figure #2, Appendix B on page 5).
- 4. The personnel shelter No. 1, with room for five-six persons, has walls constructed of pine, and rafters of beech covered with earth. (See Figure #3, Appendix B).
- 5. Heavy machine gun posts, situated at strategic points 100-400 meters apart, are built of stone 30-40 centimeters thick, or of brick plastered with cement. These posts are open on top. (See Figure #5, Appendix B on page 5).
- 6. First-aid stations are 1.2-1.3 meters deep, and have earthen walls. (See Figure #6, Appendix B on page 5).

### SECRET

STATE	ARMYEV	x	NAVY	х	AIR	x	FBI .	AEC	
							٠.	-	 <u> </u>

SECRET

-2-

# German-Made Heavy Machine Gun Nests

7. German-made heavy machine gun bunkers are built of reinforced concrete, and have an outer diameter of 5-6 meters, and an inner diameter of 2-2.5 meters. The roof is 1.6-1.8 meters thick. The bunkers are 1.5-1.8 meters high, and extend 1.5-2 meters underground. "Most" of the bunkers are surrounded by a barbed wire entanglement 7-8 meters wide and 40-50 centimeters high.

(A sketch based on a free-hand drawing of informant and showing these machine gun nests is included as Appendix C, on page 6).

# Heavy Machine Gun Nests

8. The heavy machine gun nests have walls of concrete faced brick 30-40 centimeters thick, and roofs of beech rafters covered with earth. The embrasure, inner dimensions 40-50 x 30-40 centimeters, is of reinforced concrete. The nests are placed to protect roads and dominating points in the area. They are connected with the main fortification lines by spur fortification lines.

(A sketch based on a free-hand drawing made by informant, is included as Appendix D on page 7).

# Mortar Emplacements

9. Mortar emplacements for two to five mortars are constructed with the same general plan as the heavy machine gun emplacements. All the mortar emplacements have the same dimensions, with a stone foundation of 40-50 centimeters and walls of 35-40 centimeters thick. Adjacent emplacements are placed at 7-8 meter intervals. The over-all length of a 5-mortar emplacement is 40-50 meters. The portion of the emplacement line above ground is shown in Figure #3, Appendix E. The entrances of the underground sections (see Figure #2, Appendix E) are covered with arched brick roofs which are covered with cement and 4-5 centimeters of earth. The underground portions of the line (see Figure #1, Appendix E) have wooden rafters covered with 80-90 centimeters of earth. "Some" of the emplacements have personnel shelters at both ends of the line.

(A sketch based on a free-hand drawing made by informant and showing these mortar emplacements is included as Appendix E on pages 8,9, and 10).

# Antitank Cun Emplacements

10. The portion of the emplacement above ground is shown in Figure #1,
Appendix F. The foundations are 40-50 centimeters deep depending on
the terrain, and built of stone. The brick walls are 50 centimeters
thick. Prior to 1952, roofs were made with 30-40 centimeter thick wooden
rafters, bradded together, and covered with approximately one meter of
earth. In 1952, arched brick roofs covered with earth were built. (See
Figure #2, Appendix E). Later in 1952, roofs were built of 30-35 centimeters
reinforced concrete covered with 1-1.2 meters of earth. There are no guns
currently in position.

(A sketch based on a free-hand drawing made by informant and showing these antitank guns emplacements is included as Appendix F on page 11).

SECRET

-3-

### Observation Posts

11. Platoon commanders' observation posts are placed on high land, and have an arched brick roof covered with 50-60 centimeters of earth, and walls 30-40 centimeters thick. (See Figure #1, Appendix G on page 12). Except for size, company commanders' observation points (see Figure #3, Appendix G) have the same construction as Figure #1, Appendix G.

### Personnel Shelters

12. The personnel shelters have walls 40-50 centimeters thick, and arched brick roofs covered with 1-1.2 meters of earth. The shelters can accommodate 15-20 persons. (See Figure #2, Appendix G on page 12).

### Special Observation Post

13. A special observation post, built in 1941, is located 2-3 kilometers east of Malko Sharkovo (N 42-06, E 26-49). The post has walls and a roof of reinforced concrete 40-50 centimeters thick, and is not covered with earth.

(A sketch based on a free-hand drawing made by informant and showing this post is included as Appendix H on page 13).

# Road Blocks from Knyazhevo (N 42-06, E 26-30) to Ustrem (N 42-01, E 26-27) Villages, Topolovgråd Okoliva


14. There are five road blocks on the Knyazhevo-Srem (N 42-04, E 26-29) road. The permanent blocks are built of stone and cement, and the moveable barrier is located on a 500-600 x 200-250 x 20-30 centimeter cement platform.


(A sketch based on a free-hand drawing made by informant and showing these road blocks is included as Appendix I on page 14).


15. None of the fortifications, antitank, heavy machine gun or mortar emplacements are manned at present.


25X1A 1.

SECRET










Approved For Release 2002/01/10 : CIA-RDP80-00810A001900320006-0



# Approved For Release 2002/01/10 : CIA-RDP80-00810A001900320006-0 25X1AT INCLINE 14 VISIBLE PRET F THE MORTHER EMPLANSHIPTS 3 10

Approved For Release 2002/01/10 : CIA-RDP80-00810A001900320006-0

